T2S R1W DUCHESNE COUNTY MONUMENT SURVEY RECORD 1/16 -+SEC 8 U.S.B.&M. 5-8 REFERENCE REBAR ON **FENCE** N 76°55'58" W POST 1/16 CORNER N 64°37'51 613.73' N 89°51'14" W 1314.37'— *FENCE* POST FOUND A DUCHESNE COUNTY PIPE MONUMENT WITH AN ORIGINAL MARKED STONE AT POSITION OF 1/16 CORNER 00.07,37" NORTH NOTE: SCALE: 1"=30' NOTE: THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (SECTION CORNER) LOCATED AT LAT: 40°18'07.65076"N & LONG: 109°59'30.70358"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER 0' 30' FOUND 1/2" REBAR AT POSITION OF 1/16 CORNER DESCRIPTION OF CORNER EVIDENCE FOUND POSITION OF CORNER WAS DETERMINED BY SINGLE PROPORTIONATE MEASUREMENT BETWEEN EAST—WEST 1/16 CORNERS DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER SET A 5/8" X 24" REBAR WITH A 1½" ALUMINUM CAP AT POSITION OF 1/16 CORNER PHOTO STATE PLANE COORDINATE DATA (U.S. SURVEY FEET) NAD83 UTAH CENTRAL ZONE N: 7288801.25 E: 2054305.57 NAVD88 EL: 5188.2' 40°19'12.77041" N LATITUDE: LONGITUDE: 110°00'56.02942" W ELLIPSOID HEIGHT: (GEOID 03 CONUS) 5131.61' PUBLIC LAND SURVEY SYSTEM GCDB ID NO. UT300020S0010W0_260520 PHOTO CERTIFICATION <u>Jerry D. Allred</u> , Professional Land Surveyor, State of Utah, do SIONAL LAND hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same 14895 **ALLRED** Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor ATE OF UT